
CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM





 $X.XX = \pm .01$ $X.X = \pm .25$ $X.XXX = \pm .005$ $X.XX = \pm .13$ $\frac{ANGLES}{\pm .5^{\circ}}$ DO NOT SCALE DRAWING

NOTES:

1. MAGNET PROPERTIES PER N-35SH:

Br: 11,800-12,200 G Hc: 10,800-11,500 Oe Hci: ≥20,000 Oe T max: 150 C

2. SUPPLED MAGNETIZED ACROSS THE DIAMETER

3. PARTS ARE NICKEL PLATED FOR 15hrs SALT SPRAY MIN

-		4	100	
4	3	1		Ī
1				
	COM	ACH PLIAN	I IT	

REV	DESCRIPTION	DATE	BY
В	Changed CAD, incl cert, 3D	1/30/14	ВТ

Alliance LLC 1450 CLARK DRIVE, VALPARAISO, INDIANA 46385 TOLERANCES (UNLESS OTHERWISE NOTED) DECIMAL METRIC SENSOR MACNET P(N), AL C8201

SENSOR MAGNET		P/N: ALC8301			
GRADE: N-35SH	Drwg by: BT	REV LEVEL: B			
COATING: Nickel	Appr by: DV	Appr. Dated: 05-15-2013			